



3-Phase Power transformers – IP00 & IP22



3-Phase Power Transformers.

- IP00 execution with mounting brackets
- IP22 execution with cabinet.

Connections: terminal blocks.
Impregnated windings.

Connection Types.: Δ - Δ or Δ -Y or
Y-Y or Y- Δ .

Power (VA)	Vss (%)	IP00 Dimensions				IP20 Dimensions			
		Length (mm)	Depth (mm)	Height (mm)	Weight (kg)	Length (mm)	Depth (mm)	Height (mm)	Weight (kg)
50	17	140	60	115	2.5				
100	16	140	70	115	3				
200	14	140	75	115	4				
250	12	170	85	140	5				
315	11.5	170	90	140	6				
500	10.5	170	110	140	7				
630	10	210	120	170	8				
800	9	210	130	170	12				
1000	8	210	110	220	16				
1600	7	260	120	220	19				
2000	6.8	260	140	220	24				
2500	6.7	260	150	220	26				
3150	6.5	280	150	240	31				
4000	5.5	310	160	270	37				
5000	4.8	310	210	270	45				
6300	4.7	360	220	350	65				
8000	4.1	400	240	350	70	400	300	400	
10000	4	400	270	350	75	400	300	400	85
12500	3.5	400	280	350	90				
16000	3.2	450	270	400	110				
20000	2.8	450	300	400	125	650	500	500	130
25000									

For higher Ratings (up to 160 kVA) , please contact Us



lead-free from 15.10.2005 on

ARABEL N.V.
Tel. : 00 32 2 569 15 27

Ijsbergstraat 40-42
Fax : 00 32 2 569 23 70

B-1701 ITERBEEK
email : info@arabel.be

België
Web. : www.arabel.be